

HEAT SHRINK DOME ENCLOSURE - DOME01/DOME02



El cierre de domo de Real Optic es la solución mejor diseñada e innovadora para la instalación de cableado de fibra óptica. Solo requiere su junta de sellado de goma de silicona para garantizar el buen rendimiento de sellado del cable de fibra, hasta 144 fibras de conteo de fibra. Los diferentes tamaños de entradas de cable proporcionan una gran flexibilidad para la instalación de cables.

Características y Aplicaciones

- ✓ Capacidad de hasta 144 núcleos
- ✓ Rendimiento a prueba de aire IP68
- ✓ Resistencia de aislamiento
- ✓ Resistencia de voltaje de hasta 15 kV CC

ESPECIFICACIONES

Parameters	Value
Dimensions (HxD)	450 x 230 mm
Weight (Kg)	3.80-4.20 Kg
Material	PP+GF
Max. Capacity (Fibers)	144 fibers
Maximum Number of Splice Trays	6
Capacity of Splice Tray	Max 24 single Fusion splices
Cable Entrances	5
Suitable Fiber Cable OD	Φ8mm ~ Φ17.5 (Φ24)
Sealing Structure	Heat Shrink Sealing
Sealing Rating	IP68
Operating Temperature	-40°C ~ +55°C
Impact Strength	16 N.m / IK09

COMPONENTES

Item No.	Description	Quantity	Marks
1	Cover	1 piece	Height × Diameter(mm): 450×Φ230
2	Fiber splice tray		QTY to be based on the fiber count of enclosure.
3	Base	1 set	Fixing internal part
4	Plastic hoop	1 set	Fixing bottom and cover
5	Seal fitting	1 piece	Waterproof and sealing part
6	Plastic tray holder	1 set	Fixing the splice tray and storing non-cut cable

ACCESORIOS

Item No.	Description	Quantity	Application
7	Fiber Splice Protective Tube	Core no.	Fiber fusion and protection
8	Nylon tie	Tray no.×3	Fixing fiber with protective coat
9	Pole hoop	1 set	Fixing for closure on pole
10	Labeling paper	1 piece	Fiber number mark
11	Insulating tape	1 piece	The fixing part assistant
12	EVA transparent hose	1 m	Protect fiber