



REAL OPTIC

T-OP300T/C Optical Power



Key features

- ① Energy save mode
- ② Built in VFL (optional)
- ③ Reference value storage

SPECIFICATIONS

Model	T-OP300T	T-OP300C
Measurement Range(dBm)	+10~-70dBm	+26~-50dBm
Accuracy *	± 0.2 dB	
Calibrated Wavelengths	850nm / 1300nm / 1310nm / 1490nm / 1550nm / 1625nm	
Resolution	0.01dB	
OPM Connector	2.5mm UPP and FC interchangeable (SC, ST optional)	
VFL Connector	2.5mm UPP	
Reference Value storage	Yes	
Auto Power Off	No operation in 10 minutes (can be canceled), Low battery energy	
Battery Charge	Yes	
Battery Life	Above 100 hours (1800mAH battery)	
Power Supply	AA * 2 batteries or AC/DC power supply adapter	
Size(H*W*D)	160mm *75mm * 32mm	
Weight	about 180g	
Operating Temperature	-10 -- +50 ℃, < 90%RH	
Storage Temperature	-20 -- +60 ℃, < 90%RH	

Importado y Distribuido por Real Optic Limitada

Avenida Ventisquero #1204 Modulo 18 - Renca, Chile - ventas@realoptic.com - www.realoptic.com -WP:+56996374501



REAL OPTIC

ACCESSORIES

Standard	Optional
Carrying bag*1	SC interchangeable connector*1
Calibration Certificate*1	ST interchangeable connector*1
User' s manual*1	FC male to LC female adapter*1
	AC/DC adapter*1

* at $20\pm3^{\circ}\text{C}$, CW, with FC connector, -10dBm,

For 850nm, the Min. Power measurement: -60dBm@OP300T, -40dBm@OP300C